NSN 5985-00-834-3305

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-834-3305

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.000 inches
Overall Height:
2.000 inches
Overall Width:
3.000 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
20
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 2.000 gigahertz and 4.000 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob w/dial and 1 slotted screw
Mounting Facility Pattern:
Four position circular
Mounting Facility Screw Thread Diameter:
0.138 inches
Terminal Type And Quantity:
2 connector, coaxial, female
,,,,,

NSN 5985-00-834-3305

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0