# NSN 5985-00-836-5900

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-836-5900

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

# **Tubing Wall Construction Style:**

Convolute single tubing segment

# Flange Quantity:

2

#### Flange Inside Width:

1.003 inches all flanges

### Flange Inside Height:

0.505 inches all flanges

#### Flange Outside Width:

1.625 inches all flanges

#### Flange Outside Height:

1.625 inches all flanges

#### Flange Depth:

0.438 inches all flanges

## Flange Connecting Hole Diameter:

0.109 inches all flanges single connection facility

# Voltage Standing Wave Ratio:

1.10

# Insertion Loss In Decibels:

0.08

#### Maximum Operating Pressure:

60.0 pounds per square inch gage

# Waveguide Outside Width:

1.000 inches

#### Waveguide Inside Width:

0.900 inches

# Waveguide Inside Height:

0.400 inches

## Waveguide Outside Height:

0.500 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

## Flange Style:

Cover type all flanges

# Waveguide Length:

1.500 feet

# Flexibility:

Flexible single tubing segment

## Material:

Metal single tubing segment

# NSN 5985-00-836-5900

Waveguide Assembly - Page 2 of 2



Precious Material And Location:

External surfaces silver

**Precious Material:** 

Silver

Surface Treatment:

Silver single tubing segment outside surfaces

Style Designator:

Straight type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0