NSN 5985-00-837-2355

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-837-2355

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Missile guidance and tracking set an/spg-55b

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches all flanges and 1.256 inches all flanges

Flange Inside Height:

0.628 inches all flanges and 0.631 inches all flanges

Flange Outside Width:

1.860 inches all flanges and 1.890 inches all flanges

Flange Outside Height:

1.860 inches all flanges and 1.890 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.08

Insertion Loss In Decibels:

0.20

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Length:

Between 8.969 inches and 9.031 inches

Special Features:

Frequency range 10.250 to 10, 500 mhz; operating temperature minus 20.0 to plus 150.0 degrees f; coolant passages must be capable of being pressurized to 30 psig without leakage using coolanol 45

NSN 5985-00-837-2355

Waveguide Assembly - Page 2 of 2



Flexibility:
Flexible single tubing segment
Material:
Copper alloy all flange
Precious Material And Location:
Internal surfaces gold and internal surfaces silver
Precious Material:
Gold and silver
Surface Treatment:
Gold all tubing segment and flange inside surfaces and silver all tubing segment and flange inside surfaces
Style Designator:
Straight type
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0