## NSN 5985-00-839-4406

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-839-4406
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
Between 8.125 inches and 8.375 inches
Overall Diameter:
0.781 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N .
Power Rating:
5.0 watts average and 10.0 kilowatts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+1.0/+10.0 gigahertz and +10.0/+12.4 gigahertz
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 1.000 gigahertz and 12.400 gigahertz
Special Features:
2000.0 hr life; 6000.0 ft operating alt
Test Data Document:
12436-810001-439 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Fsc Application Data:
Antennas, waveguides, and related equipment

N/a

Shelf Life:

## NSN 5985-00-839-4406

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000