

View Online at <https://aerobasegroup.com/nsn/5985-00-840-2394>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

Between 6.875 inches and 7.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.500 inches

Overall Height:

2.940 inches

Overall Width:

Between 5.438 inches and 5.562 inches

Scale Linearity:

Nonlinear

Scale Division Quantity:

50

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

N

Power Rating:

2.0 watts peak

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.8

Overall Attenuation Range In Decibels:

+0.5/+10.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

3 threaded stud

Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.20/+0.20

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Screw Thread Diameter:

0.190 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0