## NSN 5985-00-841-5008

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-841-5008

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
2.650 inches
Overall Diameter:
0.820 inches
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
5.0 watts average and 0.3 kilowatts peak
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+3.0 gigahertz
Attenuation Accuracy Reference Frequency:
3.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Temperature Sensitivity Attenuation In Decibels:
0.0001
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
68.000 grams
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 3.000 gigahertz

## NSN 5985-00-841-5008

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	ation	Data
----------------------	-----	----	------	-------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000