## NSN 5985-00-842-7890

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-842-7890

g
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.440 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.300 inches
Overall Width:
2.300 inches
Voltage Standing Wave Ratio:
1.60
Coaxial Connector Series Designation:
N
Power Rating:
2.0 kilowatts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 2.8000 gigahertz and 3.200 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.138 inches
Precious Material And Location:
Connector body silver
Precious Material:
Silver
Terminal Type And Quantity:

2 connector, coaxial, male

## NSN 5985-00-842-7890

Variable Attenuator - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0