# NSN 5985-00-842-7890

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-842-7890

# Application Design:

Transmission line

### Body Style:

Coaxial type

## Overall Length:

4.440 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.300 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.300 inches

## Overall Width:

2.300 inches

## Voltage Standing Wave Ratio:

1.60

#### **Coaxial Connector Series Designation:**

Ν

#### **Power Rating:**

2.0 kilowatts average

#### Mounting Facility Screw Thread Series Designator:

Unc

#### **Overall Attenuation Range In Decibels:**

+0.0/+20.0

#### **Attenuation Variation Method:**

Continuous

#### Mounting Facility Type And Quantity:

4 threaded hole

#### Frequency Range:

Between 2.8000 gigahertz and 3.200 gigahertz

#### Mounting Thread Quantity:

32 per inch

#### Adjustment Device Type And Quantity:

1 knob

### Mounting Facility Pattern:

Four position rectangular

# Mounting Facility Screw Thread Diameter:

0.138 inches

# Precious Material And Location:

Connector body silver

# Precious Material:

Silver

# Terminal Type And Quantity:

2 connector, coaxial, male

# NSN 5985-00-842-7890

Variable Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0

