NSN 5985-00-843-4906

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-843-4906 **Application Design:** Audio **Body Diameter:** 2.750 inches **Schematic Diagram Designator: Distance Between Mounting Facility Centers:** 1.500 inches **Power Rating:** 1.0 watts average **Mounting Facility Screw Thread Series Designator:** Unc **Overall Attenuation Range In Decibels:** +0.0/+100.0 **Attenuation Variation Method:** Stepped **Step Position Quantity:** 10 **Attenuation Per Step In Decibels:** 10.0 **Mounting Facility Type And Quantity:** 2 threaded hole Frequency Range: Between 0.000 kilohertz and 200.000 kilohertz **Overall Attenuation Accuracy In Decibels:** -0.50/+0.50 **Mounting Thread Quantity:** 32 per inch **Mounting Facility Pattern:** Two position in-line **Mounting Facility Screw Thread Diameter:** 0.164 inches Impedance Rating In Ohms: 600.0 input-output **Special Features:** Completely shielded in a dust proof and vibration brass proof case **Terminal Type And Quantity:** 5 tab, solder lug Shelf Life: N/a

Unit Of Measure:

NSN 5985-00-843-4906

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0