NSN 5985-00-843-4907

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-843-4907 **Application Design:** Audio **Body Style:** Cylindrical w/rear terminals **Overall Length:** 1.625 inches **Body Length:** 1.250 inches **Overall Diameter:** 0.688 inches **Schematic Diagram Designator:** "t" **Distance Between Mounting Facility Centers:** 1.500 inches **Power Rating:** 1.0 watts average **Mounting Facility Screw Thread Series Designator:** Unc **Overall Attenuation Range In Decibels:** +0.0/+10.0 **Attenuation Variation Method:** Stepped **Step Position Quantity: Attenuation Per Step In Decibels:** 1.0 **Mounting Facility Type And Quantity:** 2 threaded hole Frequency Range: Between 0.000 kilohertz and 200.000 kilohertz **Overall Attenuation Accuracy In Decibels:** -0.10/+0.10 **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 slotted screw **Mounting Facility Pattern:** Two position in-line **Mounting Facility Screw Thread Diameter:**

0.164 inchesImpedance Rating In Ohms:600.0 input-output

NSN 5985-00-843-4907

Variable Attenuator - Page 2 of 2



| Special | Features: |
|----------------|-----------|
|----------------|-----------|

Completely shield in a dust proof and vibration brass proof case

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0