NSN 5985-00-856-5641



Fixed Attenuator - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5985-00-856-5641
Application Design:
Transmission line
Body Material:
Metal
Body Style:
1b round, terminal/terminals in opposite surface
Body Surface Treatment:
Silver plated, qq-s-365
Overall Length:
2.500 inches
Overall Diameter:
Between 0.880 inches and 0.900 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Hn
Power Rating:
2.4 watts average and 2.0 kilowatts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+2.5 gigahertz
Attenuation Accuracy Reference Frequency:
2.5 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 2.500 gigahertz

Precious Material And Location:

Body surfaces silver

NSN 5985-00-856-5641 Fixed Attenuator - Page 2 of 2



Precious Material:	
Silver	
Fsc Application Data:	
Antennas, waveguides, and related equipment	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A20000