## NSN 5985-00-856-6293

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-856-6293

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Body Surface Treatment:
Silver
Overall Length:
2.690 inches
Overall Diameter:
0.830 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
N Power Rating:
•
Power Rating:
Power Rating: 2.0 watts average
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 6.0
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range:
Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels: 6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz Attenuation Accuracy Reference Frequency:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz Attenuation Accuracy Reference Frequency: 4.5 gigahertz
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels:
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz  Attenuation Accuracy Reference Frequency: 4.5 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz  Attenuation Accuracy Reference Frequency: 4.5 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Connection Type Per Function:
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz  Attenuation Accuracy Reference Frequency: 4.5 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Connection Type Per Function:  Female output and male input
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz  Attenuation Accuracy Reference Frequency: 4.5 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Connection Type Per Function: Female output and male input Unpackaged Unit Weight:
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz  Attenuation Accuracy Reference Frequency: 4.5 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Connection Type Per Function: Female output and male input Unpackaged Unit Weight: 2.800 ounces
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz  Attenuation Accuracy Reference Frequency: 4.5 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Connection Type Per Function: Female output and male input  Unpackaged Unit Weight: 2.800 ounces  Mounting Method:
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz  Attenuation Accuracy Reference Frequency: 4.5 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Connection Type Per Function: Female output and male input Unpackaged Unit Weight: 2.800 ounces  Mounting Method: Connector
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  6.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz  Attenuation Accuracy Reference Frequency: 4.5 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Connection Type Per Function: Female output and male input Unpackaged Unit Weight: 2.800 ounces  Mounting Method: Connector Terminal Type And Quantity:

## **NSN 5985-00-856-6293** Fixed Attenuator - Page 2 of 2



<b>Precious Material And Location:</b>
Body surfaces silver
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A20000