NSN 5985-00-869-8297

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-869-8297

| Application Design: |
|--|
| Transmission line |
| Body Material: |
| Metal |
| Body Style: |
| Err-090 |
| Body Surface Treatment: |
| Any acceptable |
| Overall Length: |
| 1.875 inches |
| Overall Diameter: |
| 0.547 inches |
| Operating Tempurature Range: |
| -55.0/+100.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.20 |
| Input Impedance Rating In Ohms: |
| 52.5 |
| Output Impedance Rating In Ohms: |
| 52.5 |
| Coaxial Connector Series Designation: |
| Bnc |
| Rf Signal Attenuation In Decibels: |
| 2.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+1.0 gigahertz |
| Attenuation Accuracy Reference Frequency: |
| 1.0 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.50/+0.50 |
| Connection Type Per Function: |
| Female input and male output |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 1.000 gigahertz |
| Fsc Application Data: |
| Antennas, waveguides, and related equipment |
| Shelf Life: |
| N/a |
| |

NSN 5985-00-869-8297

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000

