

View Online at <https://aerobasegroup.com/nsn/5985-00-877-3705>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches second flange and 0.707 inches second flange

Flange Inside Height:

0.392 inches second flange and 0.396 inches second flange

Flange Outside Width:

1.298 inches second flange and 1.328 inches second flange

Flange Outside Height:

1.298 inches second flange and 1.328 inches second flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Flange Connecting Hole Diameter:

0.144 inches first flange all connection facilities and 0.147 inches first flange all connection facilities

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches second flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

2.000 feet

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all flange

Surface Treatment:

Any acceptable all flange outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc second flange all connection facilities

Fsc Application Data:

Test set, radar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0