NSN 5985-00-881-9391

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-881-9391

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.670 inches
Overall Height:
3.848 inches
Overall Width:
3.130 inches
First Flat Length:
0.300 inches
Flat Height:
0.215 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.170 inches
Distance Between Mounting Facility Centers:
1.250 inches
Operating Tempurature Range:
-0.0/+70.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Coaxial Connector Series Designation:
Bnc
Power Rating:
400.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+100.0
Attenuation Accuracy Reference Frequency:
100.0 megahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:

10.0

NSN 5985-00-881-9391

Variable Attenuator - Page 2 of 2



Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 10.000 megahertz and 500.000 megahertz **Overall Attenuation Accuracy In Decibels:** -0.09/+0.09 **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 shaft **Mounting Facility Pattern:** Two position in-line **Shaft Type:** Round, flatted **Mounting Facility Screw Thread Diameter:** 0.164 inches Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, female Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Yes - demil/mli

Fiig: A223a0