NSN 5985-00-901-1521

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-901-1521

| Application Design: |
|--|
| Transmission line |
| Body Material: |
| Brass |
| Body Style: |
| Err-090 |
| Body Surface Treatment: |
| Silver plated |
| Overall Length: |
| Between 2.660 inches and 2.720 inches |
| Overall Diameter: |
| 0.580 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.30 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Ν |
| Power Rating: |
| 2.0 watts average and 3.0 kilowatts peak |
| Rf Signal Attenuation In Decibels: |
| 1.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+5.0 gigahertz |
| Attenuation Accuracy Reference Frequency: |
| 4.5 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.10/+0.10 |
| Frequency Sensitivity Attenuation In Decibels: |
| 0.20 |
| Connection Type Per Function: |
| Female output and male input |
| Unpackaged Unit Weight: |
| 3.200 ounces |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| |

NSN 5985-00-901-1521

Fixed Attenuator - Page 2 of 2



Frequency Range:

Between 0.000 hertz and 5.000 gigahertz

Precious Material And Location:

Body external surfaces silver

Precious Material:

Silver

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A20000