NSN 5985-00-901-6221

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-901-6221 **Application Design:** Waveguide **Body Material:** Aluminum alloy **Body Style:** Waveguide type **Overall Length:** Between 6.490 inches and 6.510 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 4.235 inches and 4.245 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** Between 3.355 inches and 3.365 inches **Overall Height:** Between 4.110 inches and 4.140 inches **Overall Width:** Between 3.840 inches and 3.920 inches **Unthreaded Mounting Hole Diameter:** 0.173 inches **Power Rating:** 1.0 watts average Waveguide Flange Type: Cover **Overall Attenuation Range In Decibels:** +0.0/+15.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 unthreaded hole Frequency Range: Between 8.500 gigahertz and 10.000 gigahertz **Adjustment Device Type And Quantity:** 1 electronic, programmable **Mounting Facility Pattern:** Four position rectangular **Terminal Type And Quantity:** 2 flange Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5985-00-901-6221

Variable Attenuator - Page 2 of 2



Fiig:

A223a0