## NSN 5985-00-901-7897

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-901-7897

Application Design:
Transmission line
Body Style:
Cylindrical w/side terminals
Overall Length:
4.750 inches
Overall Width:
2.656 inches
Body Diameter:
2.250 inches
Shaft Diameter:
Between 0.249 inches and 0.251 inches
Shaft Length:
Between 0.922 inches and 0.953 inches
Body Length:
3.812 inches
Distance Between Mounting Facility Centers:
1.500 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Power Rating:
1.5 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+100.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 525.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

1 shaft

## NSN 5985-00-901-7897

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0