NSN 5985-00-906-6120

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-906-6120

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.240 inches and 1.260 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 1.802 inches and 1.822 inches
Overall Height:
3.750 inches
Overall Width:
1.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.480 inches
Unthreaded Mounting Hole Diameter:
Between 0.138 inches and 0.146 inches
End Application:
Wsr-74c radar, lwr
Voltage Standing Wave Ratio:
1.35
Coaxial Connector Series Designation:
N
Power Rating:
4.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+30.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 5.400 gigahertz and 5.900 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.25/+0.25
Adjustment Device Type And Quantity:

1 shaft

NSN 5985-00-906-6120

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Four position rectangular

Shaft Type:

Round, slotted

Terminal Type And Quantity:

1 connector, coaxial, female and 1 connector, coaxial, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0