NSN 5985-00-907-2421

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-907-2421

| Application Design: |
|----------------------------------------------|
| Transmission line |
| Body Material: |
| Any acceptable |
| Body Style: |
| Err-090 |
| Overall Length: |
| 2.690 inches |
| Overall Diameter: |
| 0.830 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.30 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| N |
| Power Rating: |
| 2.0 watts average and 2.0 kilowatts peak |
| Rf Signal Attenuation In Decibels: |
| 10.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+4.5 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.05/+0.05 |
| Connection Type Per Function: |
| Female output and male input |
| Mounting Method: |
| Terminal |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 4.500 gigahertz |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

NSN 5985-00-907-2421

Fixed Attenuator - Page 2 of 2



Fiig:

A20000