

View Online at <https://aerobasegroup.com/nsn/5985-00-910-9839>

Unable To Decode:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches first flange and 0.904 inches first flange

Flange Inside Height:

0.396 inches first flange and 0.404 inches first flange

Flange Outside Width:

1.610 inches first flange and 1.640 inches first flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Inside Diameter:

1.406 inches first flange and 1.437 inches first flange

Flange Depth:

0.423 inches first flange and 0.453 inches first flange

Voltage Standing Wave Ratio:

1.35

Insertion Loss In Decibels:

1.50

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Flange Style:

Choke type first flange

Material:

Aluminum alloy 6061 single tubing segment

Surface Treatment:

Paint single tubing segment and flange outside surfaces

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0