

View Online at <https://aerobasegroup.com/nsn/5985-00-914-8256>

Application Design:

Waveguide

Body Material:

Copper alloy

Body Style:

Rectangular, terminal/terminals on opposite surfaces

Overall Length:

7.100 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.994 inches

Overall Height:

Between 1.610 inches and 1.640 inches

Overall Width:

Between 1.610 inches and 1.640 inches

Mounting Hole/stud Quantity:

8

Inside Width:

0.705 inches

Unthreaded Mounting Hole Diameter:

0.144 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.956 inches

Inside Height:

0.394 inches

Voltage Standing Wave Ratio:

1.15

Rf Signal Attenuation In Decibels:

20.0

Voltage Standing Wave Ratio Frequency Range:

+12.4/+18.0 gigahertz

Waveguide Flange Type:

Cover

Waveguide Flange Designation:

Ug-419/u

Attenuation Accuracy In Decibels:

-0.50/+0.50

Waveguide Designation:

Rg-91/u

Mounting Method:

Terminal w/mounting holes

Terminal Type And Quantity:

2 flange

Frequency Range:

Between 12.400 gigahertz and 18.000 gigahertz

Specification Data:

18876-7913122 manufacturers specification control

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000