## NSN 5985-00-919-1148

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-919-1148

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange single connection facility

**Thread Direction:** 

Right-hand first flange single connection facility

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.062 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.625 inches second flange

Flange Outside Height:

1.625 inches first flange

Flange Depth:

0.438 inches second flange

#### Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

**Voltage Standing Wave Ratio:** 

1.10

**Insertion Loss In Decibels:** 

10.00

#### **Maximum Operating Pressure:**

60.0 pounds per square inch gage

**Waveguide Outside Width:** 

1.000 inches

**Thread Size:** 

0.164 inches first flange single connection facility

Waveguide Inside Width:

0.900 inches

**Waveguide Inside Height:** 

0.400 inches

**Waveguide Outside Height:** 

0.500 inches

### Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

# **NSN 5985-00-919-1148** Waveguide Assembly - Page 2 of 2



Waveguide Length:
1.500 feet
Flexibility:
Flexible single tubing segment
Material:
Aluminum alloy all flange
Surface Treatment:
Any acceptable all flange outside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc first flange single connection facility
Specification Data:
81349-mil-w-287/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0