NSN 5985-00-919-5444

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-919-5444

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
8.687 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.718 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.843 inches
Overall Height:
1.968 inches
Overall Width:
3.312 inches
Coaxial Connector Series Designation:
N
Power Rating:
200.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+5.0/+90.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 1.000 gigahertz and 2.000 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
4 connector, coaxial, female
Shelf Life:

N/a

NSN 5985-00-919-5444

Variable Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A223a0