

View Online at <https://aerobasegroup.com/nsn/5985-00-920-6624>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Interlocked single tubing segment

**Tubing Twist Type:**

Twistable single tubing segment

**Tubing Twist Angle In Deg:**

120.0 single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.003 inches all flanges

**Flange Inside Height:**

0.505 inches all flanges

**Flange Outside Width:**

1.625 inches all flanges

**Flange Outside Height:**

1.625 inches all flanges

**Flange Depth:**

0.438 inches all flanges

**Flange Connecting Hole Diameter:**

0.144 inches all flanges single connection facility

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.10

**Maximum Operating Pressure:**

15.0 pounds per square inch gage

**Waveguide Outside Width:**

1.000 inches

**Waveguide Inside Width:**

0.900 inches

**Waveguide Inside Height:**

0.400 inches

**Waveguide Outside Height:**

0.500 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges single connection facility

**Flange Style:**

Cover type all flanges

**Waveguide Length:**

6.938 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Copper all flange

**Style Designator:**

Straight type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0