## NSN 5985-00-920-6704

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:



View Online at https://aerobasegroup.com/nsn/5985-00-920-6704

Steel, stainless
Body Style:
1b round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
2.656 inches
Overall Diameter:
0.812 inches
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 300.0 watts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+3.0 gigahertz
Attenuation Accuracy Reference Frequency:
3.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Unpackaged Unit Weight:
2.400 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 3.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a

## NSN 5985-00-920-6704

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000