

View Online at <https://aerobasegroup.com/nsn/5985-00-927-6058>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.255 inches second flange

**Flange Inside Height:**

0.630 inches second flange

**Flange Outside Width:**

1.860 inches second flange and 1.890 inches second flange

**Flange Outside Height:**

1.860 inches second flange and 1.890 inches second flange

**Flange Inside Diameter:**

1.610 inches first flange and 1.640 inches first flange

**Flange Depth:**

0.610 inches first flange and 0.640 inches first flange

**Flange Connecting Hole Diameter:**

0.169 inches second flange single connection facility

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.30

**Thready Qty Per Inch (tpi):**

32 first flange all connection facilities

**Maximum Operating Pressure:**

15.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 1.246 inches and 1.254 inches

**Thread Size:**

0.164 inches first flange all connection facilities

**Waveguide Inside Width:**

Between 1.118 inches and 1.126 inches

**Waveguide Inside Height:**

Between 0.493 inches and 0.501 inches

**Waveguide Outside Height:**

Between 0.621 inches and 0.629 inches

**Waveguide Longer Offset Distance:**

Between 7.920 inches and 8.000 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Offset Distance:**

Between 3.260 inches and 3.340 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Copper alloy all tubing segment and flange

**Precious Material And Location:**

Waveguide internal surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Nickel all flange outside surfaces

**Style Designator:**

Bend type

**Thread Series Designator:**

Unc first flange all connection facilities

**Fsc Application Data:**

Waveguides

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0