

View Online at <https://aerobasegroup.com/nsn/5985-00-927-9873>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.122 inches all flanges

Flange Inside Height:

0.497 inches all flanges

Flange Outside Width:

1.875 inches all flanges

Flange Outside Height:

1.875 inches all flanges

Flange Inside Diameter:

1.625 inches all flanges

Flange Depth:

0.625 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.08

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches second flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

Flange Style:

Choke type all flanges

Waveguide Length:

2.430 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber single tubing jacket

Surface Treatment:

Any acceptable single tubing segment outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc second flange single connection facility

Fsc Application Data:

Radar fire control nonairborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0