NSN 5985-00-928-0210

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-928-0210

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 first bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches second flange

Flange Inside Height:

0.394 inches second flange

Flange Outside Width:

1.313 inches second flange

Flange Outside Height:

1.313 inches second flange

Flange Depth:

0.375 inches first flange

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.15

Maximum Operating Pressure:

45.0 pounds per square inch gage

Waveguide Outside Width:

0.702 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

0.622 inches

Waveguide Inside Height:

0.311 inches

Waveguide Outside Height:

0.391 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

NSN 5985-00-928-0210 Waveguide Assembly - Page 2 of 2



Waveguide Length:
1.333 feet
Waveguide Center To Center Distance:
2.375 inches
Flexibility:
Rigid single tubing segment
Material:
Copper single tubing segment
Surface Treatment:
Any acceptable single tubing segment all surfaces
Style Designator:
Offset bend type
Thread Series Designator:
Unc first flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
Yes - demil/mli
Fiig:
A073a0