NSN 5985-00-930-3498

Variable Attenuator - Page 1 of 2

Application Design:

View Online at https://aerobasegroup.com/nsn/5985-00-930-3498



Audio
Overall Length:
1.562 inches
Shaft Diameter:
Between 0.249 inches and 0.251 inches
Shaft Length:
0.313 inches
Overall Diameter:
0.953 inches
Schematic Diagram Designator:
Bridged "t"
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.1
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches
Impedance Rating In Ohms:
600.0 input-output
Supplementary Features:
Two-section
Terminal Type And Quantity:
6 tab, solder lug
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a

NSN 5985-00-930-3498

Variable Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0

