## NSN 5985-00-930-4211

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-930-4211

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
2.187 inches
Overall Diameter:
Any acceptable
Operating Tempurature Range:
-20.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
2.0 watts average and 2.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+2.5 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Frequency Sensitivity Attenuation In Decibels:
Not rated
Temperature Sensitivity Attenuation In Decibels:
Not rated
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 2.500 gigahertz
2 connector Frequency Range:

## NSN 5985-00-930-4211

Fixed Attenuator - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000