

View Online at <https://aerobasegroup.com/nsn/5985-00-931-0120>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Interlocked single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.705 inches all flanges

**Flange Inside Height:**

0.394 inches all flanges

**Flange Outside Width:**

1.313 inches all flanges

**Flange Outside Height:**

1.313 inches all flanges

**Flange Depth:**

0.313 inches all flanges

**Flange Connecting Hole Diameter:**

0.144 inches all flanges all connection facilities

**Voltage Standing Wave Ratio:**

1.15

**Insertion Loss In Decibels:**

0.20

**Maximum Operating Pressure:**

60.0 pounds per square inch gage

**Waveguide Outside Width:**

0.702 inches

**Waveguide Inside Width:**

0.622 inches

**Waveguide Inside Height:**

0.311 inches

**Waveguide Outside Height:**

0.391 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges all connection facilities

**Flange Style:**

Cover type all flanges

**Waveguide Length:**

1.500 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Rubber single tubing jacket

**Precious Material And Location:**

Flange and tubing inside surface silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver all tubing segment and flange inside surfaces

**Style Designator:**

Straight type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0