

View Online at <https://aerobasegroup.com/nsn/5985-00-933-5299>

**Unable To Decode:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**End Application:**

Missile guidance and tracking set an/spg-55b

**Tubing Wall Construction Style:**

Corrugated single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

2.002 inches second flange and 2.005 inches second flange

**Flange Inside Height:**

1.002 inches second flange and 1.005 inches second flange

**Flange Outside Diameter:**

3.610 inches second flange and 3.640 inches second flange

**Flange Depth:**

0.923 inches first flange and 0.953 inches first flange

**Flange Connecting Hole Diameter:**

0.199 inches second flange all connection facilities and 0.203 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.10

**Thready Qty Per Inch (tpi):**

32 first flange all connection facilities

**Maximum Operating Pressure:**

40.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 1.995 inches and 2.005 inches

**Thread Size:**

0.190 inches first flange all connection facilities

**Waveguide Inside Width:**

Between 1.867 inches and 1.877 inches

**Waveguide Inside Height:**

Between 0.867 inches and 0.877 inches

**Waveguide Outside Height:**

Between 0.995 inches and 1.005 inches

**Flange Connecting Facility And Quantity:**

8 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Length:**

Between 9.938 inches and 10.063 inches

**Special Features:**

Silver plated on internal surface of waveguide

**Flexibility:**

Flexible single tubing segment

**Material:**

Rubber natural single tubing jacket

**Precious Material And Location:**

Internal surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Chromate all flange outside surfaces and chromate zinc all flange outside surfaces and enamel all flange outside surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unf first flange all connection facilities

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0