# NSN 5985-00-934-0153

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-934-0153

Transmission line

**Body Style:** 

Coaxial type

## **Overall Length:**

3.120 inches

#### **Overall Height:**

2.880 inches

**Overall Width:** 

1.810 inches

First Flat Length:

0.340 inches

#### Flat Height:

Between 0.216 inches and 0.225 inches

#### Shaft Diameter:

0.237 inches

# Shaft Length:

Between 1.090 inches and 1.150 inches

## Voltage Standing Wave Ratio:

1.50

**Coaxial Connector Series Designation:** 

Bnc

#### **Power Rating:**

100.0 milliwatts peak

#### Mounting Facility Screw Thread Series Designator:

Unf

#### Insertion Loss At Minimum Attenuation In Maximum Decibels:

6.0

#### **Overall Attenuation Range In Decibels:**

+0.0/+65.0

#### **Attenuation Variation Method:**

Continuous

#### Mounting Facility Type And Quantity:

2 threaded bushing

#### **Frequency Range:**

Between 0.000 hertz and 300.000 megahertz

# Mounting Thread Quantity:

24 per inch

### Adjustment Device Type And Quantity:

1 shaft

#### Shaft Type:

Round, flatted

# NSN 5985-00-934-0153

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.375 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A223a0