## NSN 5985-00-934-0153

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-934-0153

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.120 inches
Overall Height:
2.880 inches
Overall Width:
1.810 inches
First Flat Length:
0.340 inches
Flat Height:
Between 0.216 inches and 0.225 inches
Shaft Diameter:
0.237 inches
Shaft Length:
Between 1.090 inches and 1.150 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Bnc
Power Rating:
100.0 milliwatts peak
Mounting Facility Screw Thread Series Designator:
Unf
Insertion Loss At Minimum Attenuation In Maximum Decibels:
6.0
Overall Attenuation Range In Decibels:
+0.0/+65.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 threaded bushing
Frequency Range:
Between 0.000 hertz and 300.000 megahertz
Mounting Thread Quantity:
24 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:

Round, flatted

## NSN 5985-00-934-0153

Variable Attenuator - Page 2 of 2



Mounting	Facility	Screw	Thread	Diameter:
----------	----------	-------	--------	-----------

0.375 inches

Impedance Rating In Ohms:

50.0 input-output

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0