## NSN 5985-00-938-1149

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-938-1149

Application Design:
Audio
Body Style:
Cylindrical w/rear terminals
Overall Length:
2.406 inches
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.375 inches
Shaft Length:
0.500 inches
Body Length:
1.906 inches
Overall Diameter:
1.291 inches
Schematic Diagram Designator:
"t"
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Power Rating:
2.25 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+67.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Frequency Range:
Between 0.000 hertz and 20.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-6.70/+6.70
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round

## NSN 5985-00-938-1149

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter	Mounting	a Facility	Screw	Thread	Diameter
---	----------	------------	-------	--------	----------

0.375 inches

Impedance Rating In Ohms:

2000.0 input-output

**Test Data Document:** 

03538-77c707830 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A223a0