# NSN 5985-00-948-7089

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-948-7089

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

## Thread Class:

2b first flange all connection facilities

# **Thread Direction:**

Right-hand first flange all connection facilities

## **Tubing Wall Construction Style:**

Corrugated single tubing segment

## **Tubing Twist Type:**

Twistable single tubing segment

# Flange Quantity:

2

## Flange Inside Width:

0.703 inches second flange and 0.707 inches second flange

## Flange Inside Height:

0.392 inches second flange and 0.396 inches second flange

## Flange Outside Width:

1.297 inches second flange and 1.327 inches second flange

# Flange Outside Height:

1.297 inches first flange and 1.327 inches first flange

## Flange Depth:

0.360 inches first flange and 0.390 inches first flange

## Flange Connecting Hole Diameter:

0.142 inches second flange all connection facilities and 0.146 inches second flange all connection facilities

## Voltage Standing Wave Ratio:

1.05

**Insertion Loss In Decibels:** 

0.30

#### Maximum Operating Pressure:

45.0 pounds per square inch gage

#### Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

#### **Thread Size:**

0.138 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 0.620 inches and 0.625 inches

## Waveguide Inside Height:

Between 0.309 inches and 0.314 inches

#### Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

# NSN 5985-00-948-7089

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Length: 12.000 inches Flexibility: Flexible single tubing segment Material: Copper alloy all tubing segment and flange **Precious Material And Location:** External surfaces silver **Precious Material:** Silver Surface Treatment: Silver single tubing segment outside surfaces **Style Designator:** Straight type **Thread Series Designator:** Unc first flange all connection facilities **Fsc Application Data:** Antennas, waveguides, and related equip. Shelf Life: N/a Unit Of Measure: ---Demilitarization:

No

Fiig:

A073a0