NSN 5985-00-951-1638

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-951-1638

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.218 inches
Overall Height:
2.500 inches
Overall Width:
2.343 inches
Distance Between Mounting Facility Centers:
1.250 inches
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Bnc
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
0.2 Overall Attenuation Range In Decibels:
· · ·
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+50.0
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity:
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels:
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range:
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 hertz and 900.000 megahertz
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 hertz and 900.000 megahertz Mounting Thread Quantity:
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 hertz and 900.000 megahertz Mounting Thread Quantity: 40 per inch
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 hertz and 900.000 megahertz Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+50.0 Attenuation Variation Method: Stepped Step Position Quantity: 6 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 hertz and 900.000 megahertz Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity: 1 knob

0.112 inches

NSN 5985-00-951-1638

Variable Attenuator - Page 2 of 2



lm	pedance	Ratino	ı In Ω	hms:
	pedance	, ixatiiic	🗸	ıııııə.

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0