NSN 5985-00-954-5469



| Tixed Attendator Tage For 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5985-00-954-5469 |
| Application Design: |
| Transmission line |
| Body Material: |
| Any acceptable |
| Body Style: |
| 1b round, terminal/terminals in opposite surface |
| Body Surface Treatment: |
| Silver plated, qq-s-365 |
| Overall Length: |
| Between 2.150 inches and 2.250 inches |
| Overall Diameter: |
| Between 0.530 inches and 0.630 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.20 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Bnc |
| Power Rating: |
| 2.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 12.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+3.0 gigahertz |
| Connection Type Per Function: |
| Female output and male input |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |

Between 0.000 hertz and 3.000 gigahertz

Special Features:

Operating altitude 15000 ft

Precious Material And Location:

External surfaces silver

Precious Material:

Silver

NSN 5985-00-954-5469

Fixed Attenuator - Page 2 of 2



| | Fs | СΑ | ppl | icat | ion | Data: |
|--|----|----|-----|------|-----|-------|
|--|----|----|-----|------|-----|-------|

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000