## NSN 5985-00-954-5469



Tixed Attendator Tage For 2
View Online at https://aerobasegroup.com/nsn/5985-00-954-5469
Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
1b round, terminal/terminals in opposite surface
Body Surface Treatment:
Silver plated, qq-s-365
Overall Length:
Between 2.150 inches and 2.250 inches
Overall Diameter:
Between 0.530 inches and 0.630 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
12.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+3.0 gigahertz
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:

Between 0.000 hertz and 3.000 gigahertz

**Special Features:** 

Operating altitude 15000 ft

**Precious Material And Location:** 

External surfaces silver

**Precious Material:** 

Silver

## NSN 5985-00-954-5469

Fixed Attenuator - Page 2 of 2



	Fs	СΑ	ppl	icat	ion	Data:
--	----	----	-----	------	-----	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000