## NSN 5985-00-959-1565

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-959-1565 **Body Style:** Cylindrical w/side terminals Overall Length: 1.687 inches **Overall Width:** 1.288 inches Flat Height: 0.216 inches **Body Diameter:** 0.953 inches **Shaft Diameter:** 0.250 inches **Bushing Length:** 0.250 inches **Shaft Length:** 0.500 inches **Body Length:** 0.937 inches **Operating Tempurature Range:** -55.0/+70.0 degrees celsius **End Application:** C-5 galaxy, f-16, f-4 phantom, c-141 starlifter, c-135 stratolifter, t-38 aircraft. Uh-60a/uh-60d helicopter. F4n aircraft. **Power Rating:** 1.0 watts average **Mounting Facility Screw Thread Series Designator:** Unef **Overall Attenuation Range In Decibels:** +0.0/+61.0 **Mounting Facility Type And Quantity:** 1 threaded bushing **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 shaft **Shaft Type:** Round, flatted

**Criticality Code Justification:** 

Feat

**Mounting Facility Screw Thread Diameter:** 

0.375 inches

Impedance Rating In Ohms:

1200.0 input-output

## NSN 5985-00-959-1565

Variable Attenuator - Page 2 of 2



Special	Features:
---------	-----------

Weapon system essential

**Terminal Type And Quantity:** 

4 tab, solder lug

**Fsc Application Data:** 

Antennas, waveguides, and related equip.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0