NSN 5985-00-961-5986

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-961-5986
Cross Sectional Shape:
Internal, rectangular external, rectangular
Tubing Wall Construction Style:
Seamless single tubing segment
Tubing Twist Type:
Straight twist single tubing segment
Tubing Twist Angle In Deg:
62.0 single tubing segment
Flange Quantity:
2
Flange Inside Width:
1.253 inches all flanges
Flange Inside Height:
0.628 inches all flanges
Flange Outside Width:
1.875 inches all flanges
Flange Outside Height:
1.875 inches all flanges
Flange Depth:
0.438 inches all flanges
Flange Connecting Hole Diameter:
0.169 inches all flanges single connection facility and 0.172 inches all flanges single connection facility
Voltage Standing Wave Ratio:
1.08
Waveguide Outside Width:
1.250 inches
Waveguide Inside Width:
1.122 inches
Waveguide Inside Height:
0.497 inches
Waveguide Outside Height:
0.625 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole all flanges single connection facility
Flange Style:
Cover type all flanges
Waveguide Length:
9.000 inches
Special Features:

Furnished with two tube fittings Flexibility:

Flexible single tubing segment

NSN 5985-00-961-5986

Waveguide Assembly - Page 2 of 2



Material:
Copper alloy single tubing segment
Precious Material And Location:
Tubing internal surfaces gold and flange internal surfaces gold
Surface Treatment:
Gold single tubing segment inside surfaces
Style Designator:
Straight type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0