NSN 5985-00-973-0177

Electrical Dummy Load - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-00-973-0177

Ambient Tempurature In Deg Celsius At Full Rated Power:
56.0
Overall Length:
10.225 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches
Overall Height:
4.080 inches
Overall Width:
4.080 inches
Impedance Rating In Ohms:
50.0
Body Length:
6.250 inches
Frequency Range Rating:
+0.600/+1.850 kilohertz
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
C
Connector End Design:
Male
Power Rating:
Power Rating: 50.000 watts average
-
50.000 watts average
50.000 watts average Voltage Standing Wave Ratio Frequency Range:
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type:
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position:
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method:
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Style Designator:
50.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted
Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted Shelf Life:
Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted Shelf Life: N/a
Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted Shelf Life: N/a
Voltage Standing Wave Ratio Frequency Range: +0.600/+1.850 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Style Designator: Rf connector, 4 hole mounted Shelf Life: N/a Unit Of Measure:

A19800