

View Online at <https://aerobasegroup.com/nsn/5985-00-975-6305>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

4.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches

Overall Height:

2.060 inches

Overall Width:

4.500 inches

Unthreaded Mounting Hole Diameter:

0.154 inches

Voltage Standing Wave Ratio:

1.80 and 1.40

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 50.0 watts peak

Insertion Loss At Minimum Attenuation In Maximum Decibels:

6.0

Overall Attenuation Range In Decibels:

+0.0/+63.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 0.925 gigahertz and 1.225 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Pattern:

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Test Data Document:

45413-134204 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0