NSN 5985-00-979-5930



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-979-5930 **Application Design:** Audio **Body Style:** Irregular **Center To Center Distance Between Mounting Facilities Parallel To Width:** 6.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 4.000 inches **Schematic Diagram Designator:** Unbalanced "II" **Power Rating:** 0.2 watts average **Mounting Facility Screw Thread Series Designator:** Unc **Overall Attenuation Range In Decibels:** +0.0/+87.0 **Attenuation Variation Method:** Stepped **Step Position Quantity:** 30 **Attenuation Per Step In Decibels:** 3.0 **Mounting Facility Type And Quantity:** 4 threaded stud **Mounting Thread Quantity:** 56 per inch **Adjustment Device Type And Quantity: Mounting Facility Pattern:** Four position rectangular **Mounting Facility Screw Thread Diameter:** 0.086 inches Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, female Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5985-00-979-5930

Variable Attenuator - Page 2 of 2



Fiig:

A223a0