## NSN 5985-00-979-9154

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-979-9154

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.362 inches second flange

Flange Inside Height:

0.222 inches second flange

Flange Outside Width:

0.750 inches second flange

Flange Outside Height:

0.750 inches second flange

Flange Inside Diameter:

0.500 inches first flange

Flange Depth:

0.210 inches first flange

Flange Connecting Hole Diameter:

0.116 inches second flange all connection facilities

**Voltage Standing Wave Ratio:** 

1.07

**Insertion Loss In Decibels:** 

0.20

Thready Qty Per Inch (tpi):

40 first flange all connection facilities

**Waveguide Outside Width:** 

0.360 inches

**Thread Size:** 

0.112 inches first flange all connection facilities

Waveguide Inside Width:

0.280 inches

**Waveguide Inside Height:** 

0.140 inches

**Waveguide Outside Height:** 

0.220 inches

**Waveguide Longer Offset Distance:** 

5.040 inches

## **NSN 5985-00-979-9154** Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity:
4 unthreaded hole second flange all connection facilities
Flange Style:
Cover type second flange
Waveguide Offset Distance:
2.880 inches
Flexibility:
Rigid single tubing segment
Material:
Copper alloy all tubing segment and flange
Precious Material And Location:
Flange faces silver
Precious Material:
Silver
Surface Treatment:
Enamel all tubing segment and flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A073a0