Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-987-4481

# Thread Class:

2b mounting facility hole

# Body Style:

Rectangular

# **Overall Length:**

Between 2.288 inches and 2.320 inches

# **Overall Height:**

1.453 inches

## **Overall Width:**

0.875 inches

# **Frequency Rating:**

225.0 megahertz single frequency voltage standing wave ratio and 400.0 megahertz single frequency voltage standing wave ratio

## Switch Type:

Nontransfer

## Distance Between Mounting Facility Centers:

0.843 inches 2nd mounting facility pattern

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## End Application:

Radio set an/arc-109

# Voltage Standing Wave Ratio:

1.10 single

## Insertion Loss In Decibels:

0.20 single

## Rf Power Handling Capability:

50.0 watts average single

## Minimum Crosstalk Rating In Decibels:

40.0 single

# Actuator Operating Method:

Relay

# Actuator Voltage In Volts:

32.0

# Switch Operation Sequence:

Breaks before makes

# Switching Time:

15.0 milliseconds

# Switch Return Mechanism Type:

Fail-safe

# Pole Quantity:

1

## Throw Quantity:

2

# NSN 5985-00-987-4481

Radio Frequency Transmission Line Switch - Page 2 of 2



**Coupling Position Quantity:** 

3

#### Mounting Facility Type And Quantity:

3 threaded hole

Thread Size:

0.086 inches mounting facility hole

# Mounting Facility Pattern:

Three position in-line single mounting facility pattern

Material:

Copper body

**Precious Material And Location:** 

Contact surfaces silver

Precious Material:

Silver

#### Thread Series Designator:

Unc mounting facility hole

Shelf Life:

N/a

--

#### Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A158a0