NSN 5985-00-991-3544

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-991-3544 **Application Design:** Transmission line **Body Material:** Copper **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** 2.531 inches **Overall Diameter:** 0.812 inches **Operating Tempurature Range:** -20.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 and 1.50 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 1.0 watts average **Rf Signal Attenuation In Decibels:** 22.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+2.0 gigahertz **Attenuation Accuracy Reference Frequency:** 2.0 gigahertz **Attenuation Accuracy In Decibels:** -1.00/+1.00 **Connection Type Per Function:** Female input and male output **Unpackaged Unit Weight:** 1.500 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

Frequency Range:

Between 0.000 hertz and 2.000 gigahertz

NSN 5985-00-991-3544

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc Appl	ication	Data
----------------------	----------	---------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000