NSN 5985-00-991-3546

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-991-3546

Application Design:					
Transmission line					
Body Material:					
Aluminum alloy and copper alloy					
Body Style:					
1b round, terminal/terminals in opposite surface					
Body Surface Treatment:					
Any acceptable					
Overall Length:					
2.531 inches					
Overall Diameter:					
0.812 inches					
Operating Tempurature Range:					
-20.0/+125.0 degrees celsius					
Voltage Standing Wave Ratio:					
1.20 and 1.50					
Input Impedance Rating In Ohms:					
50.0					
Output Impedance Rating In Ohms:					
50.0					
Coaxial Connector Series Designation:					
N					
Power Rating:					
1.0 watts average					
Rf Signal Attenuation In Decibels:					
8.0					
Voltage Standing Wave Ratio Frequency Range:					
+0.0/+1.0 gigahertz and +1.0/+2.0 gigahertz					
Attenuation Accuracy Reference Frequency:					
2.0 gigahertz					
Attenuation Accuracy In Decibels:					
-1.00/+1.00					
Connection Type Per Function:					
Female input and male output					
Unpackaged Unit Weight:					
1.500 ounces					
Mounting Method:					
Connector					
Terminal Type And Quantity:					
2 connector					
Frequency Range:					
Between 0.000 hertz and 2.000 gigahertz					

NSN 5985-00-991-3546

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	ation	Data
----------------------	-----	----	------	-------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000