NSN 5985-00-991-8729



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-991-8729 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** 1.875 inches **Overall Diameter:** 0.547 inches **Schematic Diagram Designator:** Unbalanced "pi"

Operating Tempurature Range:

-55.0/+100.0 degrees celsius

Voltage Standing Wave Ratio:

voltage Clariding Wave Ratio

1.20

Input Impedance Rating In Ohms:

52.5

Output Impedance Rating In Ohms:

52.5

Coaxial Connector Series Designation:

Bnc

Power Rating:

500.0 milliwatts average

Rf Signal Attenuation In Decibels:

15.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+1.0 gigahertz

Attenuation Accuracy Reference Frequency:

1.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

NSN 5985-00-991-8729

Fixed Attenuator - Page 2 of 2



	Fsc	Ap	olication	Data:
--	-----	----	-----------	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000